



## Brief introduction

Xierengroup was founded in 1987 and now occupies a production facility of 60,000 square meters with annual sales reaching 20 million USD. Xierengroup is an integrated company with research, manufacturing, and marketing divisions. The company has its own license for import and export and acts as a domestic distributor of chemical raw materials.



Xierengroup has achieved and maintains AAA grade of credit rating. Xierengroup has been certified to the ISO9001:2000 standard. The quality all Xieren brand products are guaranteed by the PICC (the People Insurance Company of China). We regard as our historical mission to beautify the homes of our people. We respect our customers, serve our customers, and strive to continuously improve the quality of life of our people.

Xierengroup company consists of Xinxiang Xieren Industry Co., Ltd., Henan xieren safety screens Co., Ltd, and Xieren Research Center. There are 300 workers in the company including ten senior engineers and more than 90 college or university graduates. Xieren group strives to develop its own product lines. The main products include the PVC strips, PVC strip curtains, PVC strip doors, soft glass and other PVC sheest. The PVC strip curtain and soft glass are unique designs of Xierengroup and are covered by patent applications to protect our intellectual property. Xierengroup also has state of the art digital mold fabricating capability. We can produce high precision molds including very large sizes to set up production runs of products designed by our clients.



For more informations please visit :  
[Http://www.xierengroup.com](http://www.xierengroup.com)

# The largest manufacturer of pvc strips in China

### Pvc strip Benefits:

- Reduce hot/cold air loss
- Provides control for birds & flying pests
- Restricts movement of air pollutants
- Minimal maintenance
- Easy to Install
- Allows easy access for pedestrians
- Choice of grades and colours
- Bolt-on system
- A self-extinguishing product
- Hook-on system
- Strong & durable
- Sliding system

### Technical strip & sheet material data

Performance Test	Method Ref #	Strip Door Grade Standard Clear Formula P.35 Value	Strip Door Grade Super Clear Formula P.45 Value	Unit
Relative Density	DM 53 478	-1.22	-1.19	Gram/3
Softness A (DIN 53 505)		77	63	
Stitch point	DIN 53 372	Approx. 35	Approx. 45	Degrees
Falling Ball Test	Internal Test	<35 No Break	<45 No Break	Degrees
Flexibility	DIN 51 548	<35 No Break	<45 No Break	Degrees
Water Absorption	DIN 53 472	17	21	Mg
Tensile Strength	DIN 53 455	17	13	Mpa
Tensile Stress	DIN 53 455	300	420	%
Relative Resistance	DIN 53 510	>5	>2	M/mtr
Resistant to Fire	DIN 53 362	Self-extinguishing	Self-extinguishing	0
Flammability	Internal Test	Inflammable	Inflammable	0
Adhesion (Krafton)	DIN 52 210	<30 4B	0	0
Light Transmittance	—	>80	>80	%

### Fixing instructions for PVC Curtain Kit


Secure the stainless steel top track to the head of the doorframe or closest firm fixing with the screws provided.

**40% lap**  
Position the "hook on" plates 3 hooks apart.

**80% lap**  
Position the "hook on" plates 1 hook apart.

Trim each strip to length with scissors or a sharp knife and finish 15-20mm above the floor, check 72hrs after installation for stretching and re-trim if necessary.

Please note: Strips may retain the coil action for several days depending on the location of the curtain.



## HENAN XIEREN SAFETY SCREENS CO.,LTD



### Standard Clear

Product Code	Width	Thickness	Length
PSCL1M2002	200mm	2mm	50m
PSCL1M2003	200mm	3mm	50M
PSCL1M3002	300mm	2mm	50M
PSCL1M3003	300mm	3mm	50M
PSCL1M4004	400mm	4mm	50M



### Polar Clear

Product Code	Width	Thickness	Length
PSCL1M2002P	200mm	2mm	50m
PSCL1M2003P	200mm	3mm	50M
PSCL1M3002P	300mm	2mm	50M
PSCL1M3003P	300mm	3mm	50M
PSCL1M4004P	400mm	4mm	50M



### Standard Solid Black

Product Code	Width	Thickness	Length
PSCL1M2002BL	200mm	2mm	50m
PSCL1M2003BL	200mm	3mm	50M
PSCL1M3002BL	300mm	2mm	50M
PSCL1M3003BL	300mm	3mm	50M



### No colour

Product Code	Width	Thickness	Length
PSCL1M2002GC	200mm	2mm	50m
PSCL1M2003GC	200mm	3mm	50M
PSCL1M3002GC	300mm	2mm	50M
PSCL1M3003GC	300mm	3mm	50M
PSCL1M4004GC	400mm	4mm	50M



### Polar No colour

Product Code	Width	Thickness	Length
PSCL1M2002GP	200mm	2mm	50m
PSCL1M2003GP	200mm	3mm	50M
PSCL1M3002GP	300mm	2mm	50M
PSCL1M3003GP	300mm	3mm	50M
PSCL1M4004GP	400mm	4mm	50M




### Standard Double Ribbed Clear

Product Code	Width	Thickness	Length
PSCL1M2004	200mm	2mm	50m
PSCL1M3005	300mm	3mm	50M
PSCL1M4006	400mm	4mm	50M




### Polar Double Ribbed Clear

Product Code	Width	Thickness	Length
PSCL1M2004P	200mm	2mm	50m
PSCL1M3005P	300mm	3mm	50M
PSCL1M4006P	400mm	4mm	50M



### Standard Double Ribbed White

Product Code	Width	Thickness	Length
PSCL1M2004W	200mm	2mm	50m
PSCL1M3005W	300mm	3mm	50M
PSCL1M4006W	400mm	4mm	50M



### Anti-insect Yellow Double Ribbed

Product Code	Width	Thickness	Length
PSCL1M2004AY	200mm	2mm	50m
PSCL1M3005AY	300mm	3mm	50M
PSCL1M4006AY	400mm	4mm	50M



### Anti-static Green Double Ribbed

Product Code	Width	Thickness	Length
PSCL1M2004ASG	200mm	2mm	50m
PSCL1M3005ASG	300mm	3mm	50M
PSCL1M4006ASG	400mm	4mm	50M



### Welding Green

Product Code	Width	Thickness	Length
PSCL1M2002WB	200mm	2mm	50m
PSCL1M2003WB	200mm	3mm	50M
PSCL1M3002WB	300mm	2mm	50M
PSCL1M3003WB	300mm	3mm	50M
PSCL1M4004WB	400mm	4mm	50M



### Welding Bronze

Product Code	Width	Thickness	Length
PSCL1M2002WBB	200mm	2mm	50m
PSCL1M2003WBB	200mm	3mm	50M
PSCL1M3002WBB	300mm	2mm	50M
PSCL1M3003WBB	300mm	3mm	50M
PSCL1M4004WBB	400mm	4mm	50M



### Standard Yellow

Product Code	Width	Thickness	Length
PSCL1M2002Y	200mm	2mm	50m
PSCL1M2003Y	200mm	3mm	50M
PSCL1M3002Y	300mm	2mm	50M
PSCL1M3003Y	300mm	3mm	50M
PSCL1M4004Y	400mm	4mm	50M



### Anti-insect Yellow

Product Code	Width	Thickness	Length
PSCL1M2002AY	200mm	2mm	50m
PSCL1M2003AY	200mm	3mm	50M
PSCL1M3002AY	300mm	2mm	50M
PSCL1M3003AY	300mm	3mm	50M
PSCL1M4004AY	400mm	4mm	50M



### Glow-in-the-Dark

Product Code	Width	Thickness	Length
PSRD1M2002GLO	200mm	2mm	50m



### Standard Red Clear

Product Code	Width	Thickness	Length
PSRE1M2002C	200mm	2mm	50m
PSRE1M2003C	200mm	3mm	50M
PSRE1M3002C	300mm	2mm	50M
PSRE1M3003C	300mm	3mm	50M
PSRE1M4004C	400mm	4mm	50M




### Standard Solid Red

Product Code	Width	Thickness	Length
PSRE1M2002	200mm	2mm	50m
PSRE1M2003	200mm	3mm	50M
PSRE1M3002	300mm	2mm	50M
PSRE1M3003	300mm	3mm	50M
PSRE1M4004	400mm	4mm	50M



### Standard Ventilation Clear

Product Code	Width	Thickness	Length
PSCL1M2002S	200mm	2mm	50m
PSCL1M2003S	200mm	3mm	50M
PSCL1M3002S	300mm	2mm	50M
PSCL1M3003S	300mm	3mm	50M
PSCL1M4004S	400mm	4mm	50M



### Standard Grey

Product Code	Width	Thickness	Length
PSCL1M2002G	200mm	2mm	50m
PSCL1M2003G	200mm	3mm	50M
PSCL1M3002G	300mm	2mm	50M
PSCL1M3003G	300mm	3mm	50M
PSCL1M4004G	400mm	4mm	50M



### Standard Orange

Product Code	Width	Thickness	Length
PSCL1M2002O	200mm	2mm	50m
PSCL1M2003O	200mm	3mm	50M
PSCL1M3002O	300mm	2mm	50M
PSCL1M3003O	300mm	3mm	50M
PSCL1M4004O	400mm	4mm	50M



### Pvc sheets

Width	From 600mm to 1200mm
Thickness	From 1mm to 6mm
Length	as order